



LTE Cat M1/NB2 waterproof GNSS tracker supporting BLE 5.2 with up to 1 year standby time

150g (5.29oz) 170g (6.0oz) (magnet-mounted version)

-20°C ~ +60°C

87 × 51 × 30mm 3.43''(L) × 2.01''(W) × 1.18''(H) 87 × 51 × 33.5mm 3.43''(L) × 2.01''(W) × 1.32''(H) (magnetic case mounting version)

Li-Polymer 3.7V/2400 mAH

OTA Control

Scheduled Timing Report

Geo-fences

IP67 Waterproof

Vibration Feedback

Low Power Alarm

Wakeup Report

Motion Detection

Automatic Mode Switching

Temperature Monitoring

Tamper Detection

Magnetic mounting (Optional)

Use with Animal Collars

Standby Time:

Ŋ

1 Report/ Day 1 year

The GL521MG is derived from our successful GL500MG by supporting NB2 and adding Qi wireless charging and BLE. Our customers love the battery-powered GL500MG but still wanted a rechargeable version for certain scenarios. We designed this version without impacting the waterproof and robust enclosure. Adding BLE allows connectivity to diverse wireless accessories. With internal temperature and light sensors, the product is ideal for a wide range of environmental monitoring applications such as cold chain logistics, warehouse management, cargo trucking, high-value static asset monitoring and more. The GL521MG supports several mounting alternatives which use unique clip on design to securely attach the device to any asset.



GL521MG

Region	Network/Operating Band	GNSS Type	Position Accuracy (CEP)	Certificate
Worldwide	LTE Cat M1/NB2: Cat M1: LTE-FDD: B1/B2/B3/B4/B5/B8/B12/B13/ B18/B19/B20/B25/B26/B27/B28/B66/B85 Cat NB2: LTE-FDD: B1/B2/B3/B4/B5/B8/B12/B13/ B18/B19/B20/B25/B28/B66/B71/B85 EGPRS: 850/900/1800/1900 MHz	u-blox All-in-One GNSS receiver	Autonomous: < 2.5m	CE/FCC/ Verizon

Appearance



Interfaces

Power Button	ton Used for power on/off and working status checking	
LTE Antenna	Internal only	
GNSS Antenna	Internal only	
BLE Antenna	Internal only	
LED Indicators	GNSS, CEL	

Air Interface Protocol

Command Set	@Track protocol command
Transmit Protocol	TCP, UDP, SMS
Working Modes	Power saving mode for long standby time Continuous mode for emergency tracking
Scheduled Timing Report	Report position and status at preset time intervals
Geo-fences	Support up to 20 internal geo-fence regions
Low Power Alarm	Alarm when internal battery is low
Wakeup Report	Report when the device wakes up
Motion Detection	Motion detection based on internal 3-axis accelerometer
Reporting Frequency Adjustment	Intelligent adjustment of reporting frequency

LIMITED LIABILITY NOTICE

Using unapproved chargers with Queclink products may cause harm to the product and may result in battery failure, even risk of severe heat, and burst. Queclink, its distributors, and affiliates shall not bear the burden of responsibility for any damages as described here above. By using a third-party charger, you assume all responsibility for any risk, harm, and or injury.

Accessories



WTH300

BLE temperature and humidity sensor



WKF300

BLE key fob for continuously detecting the on-board status of the device



WBC300

BLE I/O expander used for engine control and locking control together with external relay



Wireless Charger Accessories Kit

The kit includes USB Type-C cable (USB-C to USB-A), USB-A charger and wireless charging pad. It's used for device charging

Parts list:

GL501_Type-C USB cable

Cable Length: 100cm; Color: black Connector Type: USB-A, USB Type-C

GL501MG_USB charger Model: RCL-U050100C

AC:100-240V; DC:5V-1A; Color: black

GL501MG_Wireless charger Model: RCL-WXC5WF

Input: 5V~1A; Output: 5V-800~1000mA



GL500M Mounting Bracket

It's used for mounting GL500 and GL501 LTE series



GL500M Battery Pack

Lithium Battery Pack 1400mAh 9V 12.6Wh 3-Cells



5-in-1 Wireless Charger Kit

The 5-in-1 wireless charger kit enables wireless charging of five compatible GL501MG products at the same time. Parts list: GL501MG 5-in-1 adapter

Wireless charging plate (excluding station) Wireless charging station (Magnetic) ×5

Charging pad ×5